



Filter housing APF163SE

Design / capacity		
Connection	Rp 2" female thread	
Nominal capacity	1300 m³/h with APE160 at 1 bar (abs.) and 20°C at 7 bar g	
Maximum capacity	2520 m³/h with APE160 at 1 bar (abs.) and 20°C at 16 bar g	
Maximum working pressure	16 bar g	
Material	Aluminium	
Operating temperature maximum	120 °C	
Coating inside / outside	Corrosion protection layer	
Colour outside	RAL 9003 (powder coated)	
Fixing element	Wing suspension	
Condensate drainage connection	Rp 1/2" female thread	
Dimensions in mm	A	744
[Dimension drawing on the last page]	B	45
	C	196
	D	195
Weight (incl. element and drainage)	12,7 Kg	
CE norm	2014/68/EU Categorie I	

Scope of supply	
Housing	APF163SE
Filter element	APE160
Condensate drainage	HAM12

Options	
Filter connection sets for 2 - 3 filters	APF-VEE-(2/3)-XL
Wall mounting brackets, including filter connecting kit	APF-WHE-(1/2/3)-XL

Capacity filter elements APE160

Type	Particle filtration [micron]	Residual oil content [mg/m³]	Working temperature [°C]		Differential pressure [mbar]			ISO classes*	
			maximum	recommended	new	moistened	replacement	particle	oil
APE160SE	0,01	-	120	50	100	-	every 6 months	1	-

Compressed air quality according ISO 8573-1:2010*

Correction factors																
Working pressure	bar g	Coefficient														
		2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
		0,38	0,50	0,63	0,75	0,88	1,00	1,12	1,25	1,37	1,49	1,62	1,74	1,86	1,98	2,10

Multiply the capacity of the filter by the correction factor in the upper table.



APE160

Design

Flow direction	From the inside out
Material end caps	Polypropylene
Support body inside and outside	Stainless steel
Filtration medium	Borosilicate microfiber fabric
Bonding end caps	Two-part epoxy resin
Material o-ring	EPDM
Distinctive characteristics	Technically silicone-free
Cavity volume at 20°C	96%
max. sterilising temperature*	145 °C

*****Recommendation:** Maximum sterilising temperature refers to the filter element only. It can be steam sterilised 50 times. Each element must be autoclaved before it can be used.

Dimensional drawing

