

## Refrigerant Dryer KT-S540

Rev 01\_0324

### Technical data sheet

Page 1 of 2

Reference conditions according to DIN/ISO 7183	Unit	Design data
Rated Air Flow max.	m <sup>3</sup> /h	540
Working pressure	bar g	7
Dewpoint	°C	+ 3
Air Inlet Temperature	°C	+ 35
Ambient Temperature	°C	+ 25

Data under Operating Conditions	Unit	Design data
Rated Air Flow max.	m <sup>3</sup> /h	540
Working Pressure max.	bar g	16
Dewpoint	°C	+ 4
Ambient temperature max.	°C	+ 50
Air Inlet Temperature max.	°C	+ 60
Pressure drop	mbar	250

General Data	Unit	Design data
Cooling	Type	Air cooled
Refrigerant	Type	R134 a
Refrigerant Quantity	Kg	1.95
Number of Heat Exchangers	Pcs.	1
Heat Exchanger	Type	Brazed plate
Heat Rejection Capacity max. at 45°C	W	3881
Compressor	Type	Hermetic
Condenser Air Flow	m <sup>3</sup> /h	1940
Working Pressure max.	bar g	16
Air Inlet Temperature max.	°C	+ 60
Condenser Fans	Pcs.	1
Fan Size	Ø mm	350
Drain Type	Type	KN1
Air Outlet Temperature	°C	25 - 30 at 35°C air inlet temperature
Relative Humidity	%	100

## Refrigerant Dryer KT-S540

Rev 01\_0324

### Technical data sheet

Page 2 of 2

Electrical Data	Unit	Design data
Total installed power	kW	1.15
Nominal operating ampacity	A	8
Voltage	V/Ph/Hz	230/1/50
Electrical protection class according IEC		IP54
Controller	Type	CAREL easy PJS8
Fuse	A	10

Dimensions and weights	Unit	Design data
Height (H)	mm	830
Length (T)	mm	855
Width (B)	mm	700
Compressed air connection size	Inch	G2 1/2" female
Total weight	Kg	129
Drain connection size	Inch	G3/8" male with hose holder for tube Ø10-12mm

### Dimensional drawings

